



## **Declaration of Conformity**

| For the following equipment |
|-----------------------------|
|-----------------------------|

Product Name: LED Driver

Model Designation: HLG-240x-yz (x=H or blank; y=12,15,20,24,30,36,42,48 or 54; z=A,B,C,AB or blank)

is herewith confirmed to comply with the requirements set out in the Council Directive, the following standards were applied:

RoHS Directive (2011/65/EU), (EU)2015/863

Energy-Related Products Directive (2009/125/EC)
Implementing measure COMMISSION REGULATION(EU) No 2019/2020

Low Voltage Directive (2014/35/EU):

TUV certificate No : R50171751 (for y=A,B,AB,Blank type)

TUV certificate No: R50171244 (for y=C type)

## **Electromagnetic Compatibility Directive (2014/30/EU):**

**EMI (Electro-Magnetic Interference)** 

Conducted emission / Radiated emission

EN IEC 55015:2019+A11:2020

 Harmonic current
 EN IEC 61000-3-2:2019
 Class C(≥50% load)

 Voltage flicker
 EN 61000-3-3:2013+A1:2019

## **EMS (Electro-Magnetic Susceptibility)**

| FΝ    | 61 | 547:2009 |  |
|-------|----|----------|--|
| _ 1 1 | v  | JT1.2003 |  |

| EN 61547:2009             |                           |                    |                                |
|---------------------------|---------------------------|--------------------|--------------------------------|
| ESD air                   | EN 61000-4-2:2009         | Level 4            | 15KV                           |
| ESD contact               | EN 61000-4-2:2009         | Level 4            | 8KV                            |
| RF field susceptibility   | EN IEC 61000-4-3:2020     | Level 2            | 3V/m                           |
| EFT bursts                | EN 61000-4-4:2012         | Level 2            | 1KV/5KHz                       |
| Surge susceptibility      | EN 61000-4-5:2014+A1:2017 | Level 4            | 2KV/Line-Line                  |
| Surge susceptibility      | EN 61000-4-5:2014+A1:2017 | Level 4            | 4KV/Line-Earth                 |
| Conducted susceptibility  | EN 61000-4-6:2014         | Level 2            | 3V                             |
| Magnetic field immunity   | EN 61000-4-8:2010         | Level 2            | 3A/m                           |
| Voltage dip, interruption | EN IEC 61000-4-11:2020    | 30% dip 10 periods | 100% interruptions 0.5 periods |

Note:

Component power supply will be operated with a final equipment. Since EMC performance will be affected by the complete installation, the final equipment manufacturers must re-qualify EMC Directive on the complete installation again.

Tests above are only to be performed with intended loads, i.e. either with LEDs or resistive load.

For guidance on how to perform these EMC tests, please refer to TDF (Technical Documentation File)

To fulfill requirements of the latest ErP regulation for lighting fixtures, this LED power supply can only be used behind a switch without permanently connected to the mains.

This Declaration is effective from serial number GC1xxxxxxx

Person responsible for marking this declaration:

MEAN WELL Enterprises Co., Ltd.

(Manufacturer Name)

No.28, Wuquan 3rd Rd., Wugu Dist., New Taipei City 24891, Taiwan

(Manufacturer Address)

Aries Jian/Director, Group R & D:

(Name / Position)

(Signature)

Alex Tsai/Director, Marketing Department:

(Name / Position)

(Signature)

Taiwan

Aug. 16th, 2021

(Place) \_\_\_

(Date)





| Declaration of Conformity  |   |   |                                      |  |  |  |  |
|--|---|---|--------------------------------------|--|--|--|--|
| For the following equipmen   | nt:   |   |                                      |  |  |  |  |
| Product Name: Switching F  | ower Supply                                   |   |                                      |  |  |  |  |
| Model Designation: HLG-240x-yz (x=H or blank; y=12,15,20,24,30,36,42,48 or 54; z=A ,B ,C or blank)   |   |   |                                      |  |  |  |  |
| is herewith confirmed to comply with the requirements set out in the Council Directive, the following standards were applied :   |   |   |                                      |  |  |  |  |
| RoHS Directive (2011   | /65/EU)、(EU)2015/863                          |   |                                      |  |  |  |  |
| Low Voltage Directive (  | 2014/35/EU):                                  |   |                                      |  |  |  |  |
| EN62368-1:2014+A11:201   | 7   | CB certificate No : D                           | certificate No: DK-91598-UL          |  |  |  |  |
| Electromagnetic Comp<br>EMI (Electro-Magnetic Int<br>Conducted emission / Rad  |   | EU) :   | Class B                              |  |  |  |  |
| Harmonic current   | EN61000-3-2:2014                              |   |                                      |  |  |  |  |
| Voltage flicker  | EN61000-3-3:2013                              |   |                                      |  |  |  |  |
| EMS (Electro-Magnetic S  | usceptibility)                                |   |                                      |  |  |  |  |
| EN55024:2010+A1:2015   | EN61000-6-2:2005                              |   |                                      |  |  |  |  |
| ESD air  | EN61000-4-2:2009                              | Level 3   | 8KV                                  |  |  |  |  |
| ESD contact  | EN61000-4-2:2009                              | Level 2   | 4KV                                  |  |  |  |  |
| RF field susceptibility  | EN61000-4-3:2006+A1:2008+                     | A2:2010 Level 3                                 | 10V/m                                |  |  |  |  |
| EFT bursts   | EN61000-4-4:2012                              | Level3  | 2KV/5KHz                             |  |  |  |  |
| Surge susceptibility   | EN61000-4-5:2014                              | Level 4   | 2KV/Line-Line                        |  |  |  |  |
| Surge susceptibility   | EN61000-4-5:2014                              | Level 4   | 4KV/Line-Earth                       |  |  |  |  |
| Conducted susceptibility   | EN61000-4-6:2014                              | Level 3   | 10V                                  |  |  |  |  |
| Magnetic field immunity  | EN61000-4-8:2010                              | Level 4   | 30A/m                                |  |  |  |  |
| Voltage dip, interruption  | EN61000-4-11:2004 >95% dip 0.5                | 5 periods 30% dip 25 pe                         | riods >95% interruptions 250 periods |  |  |  |  |
| Note:  A component power supply with load will be installed into final equipment which consists of an electronically shielded metal enclosure. Since EMC performance will be affected by the complete installation, the final equipment manufacturers must re-qualify EMC Directive on the complete installation again.  The EMC tests mentioned above are performed using a well defined metal plate to simulate said metal enclosure.  For guidance on how to perform these EMC tests, please refer to "EMI testing of component power supplies".(as available on <a href="http://www.meanwell.com">http://www.meanwell.com</a> )" and TDF (Technical Documentation File). |   |   |                                      |  |  |  |  |
| This Declaration is effective from   | om serial number HB9xxxxxxx                   |   |                                      |  |  |  |  |
| Person responsible for man   | rking this declaration:                       |   |                                      |  |  |  |  |
| MEAN WELL Enterprises (<br>(Manufacturer Name)<br>No.28, Wuquan 3rd Rd., W   | Co., Ltd.<br>/ugu Dist., New Taipei City 2489 | 1, Taiwan                                       |                                      |  |  |  |  |
| (Manufacturer Address)   | n   | -   | (a)                                  |  |  |  |  |
| Johnny Huang/Manager, Certific<br>(Name / Position)  | cation Center :(Signature)                    | Alex Tsai/Director, Market<br>(Name / Position) | eting Department : (Signature)       |  |  |  |  |

Dec. 30th, 2019

(Date)

Taiwan

(Place)